

Firefox 23.0.1
menu D7.html
プロトタイププロジェクトの結果3

```

function Calc(x,y){
    this.x = x;
    this.y = y;
}

Calc.prototype = {
    constructor: Calc,
    name: 'calc',
    func: 'non',
    arg: function (){console.log(this.x, this.y);}
}
add: function (){console.log('Can not');}
sub: function (){console.log('Can not');}
}

function Calc(x,y){
    this.x = x;
    this.y = y;
}

Calc.prototype = Object.create(Calc.prototype);
Calc.prototype.constructor = Calc;
Calc.prototype.name = 'calc';
Calc.prototype.func = 'non';
Calc.prototype.arg = function (){console.log(this.x + this.y);}
Calc.prototype.add = function (){console.log(this.x + this.y);}

function Calc(x,y){
    this.x = x;
    this.y = y;
}

Calc.prototype = Object.create(Calc.prototype);
Calc.prototype.constructor = Calc;
Calc.prototype.name = 'calc';
Calc.prototype.add = function (){console.log(this.x + (this.y + 1));}
Calc.prototype.sub = function (){console.log(this.x - this.y);}

if (new Calc(1,2).name) // calc
console.log(calc); // calc
calc.add(); // 12
calc.sub(); // Can not

function Calc(x,y){
    this.x = x;
    this.y = y;
}

Calc.prototype = Object.create(Calc.prototype);
Calc.prototype.constructor = Calc;
Calc.prototype.name = 'calc';
Calc.prototype.sub = function (){console.log(0);}

if (new Calc(1,1).name) // calc
console.log(calc); // calc
calc.add(); // 1
calc.sub(); // 0

console.log(calc);
console.log(calc);
console.log(calc);

```